

FEATURES AND BENEFITS

Climate Control Air Compressors
Simplex and Duplex Horizontal Tank Mounted .75 - 5HP

SIMPLEX COMPRESSORS

- Magnetic motor starter
- Splash lubricant system
- Horizontal ASME air receiver
- UL approved pressure switch
- OSHA approved totally enclosed belt guard
- ASME approved safety relief valve
- ASME approved discharge air service valve
- V-belt drive
- Oil level sight indicator
- Manual condensate tank drain valve
- Premium Efficiency Motors (3-phase 1HP and up only)
- Large metal intake filter-silencers (Available only from 3HP and up)

- Pressure switch (0.5 and 1HP)
- Magnetic starter included (2HP and above)
- Dial read-out pressure gauge indicator
- Factory-filled lubricant
- Optional ODP Motor 3/60/575V

DUPLEX COMPRESSORS

- NEMA-1 Alternator control panel
- Standard two power source
- 3 Position alternator switch

Optional Accessories - Shipped Loose

- Discharge Air Line Filters
- Automatic Condensate Electric Traps
- Vibration Isolator Pads
- PRV Station



TECHNICAL DATA

SIMPLEX

MODEL	HP	PUMP	TANK SIZE	CFM @ 80 PSI	WEIGHT (Lbs.)
3SA3	0.75	ES06	30	2.1	165
3SG5	1.5	E23	30	4.1	220
6SJ7	3	ES30	60	7.5	350
8SN8	3	ES50	80	11.3	480
8SN9	5	ES50	80	15.2	485

DUPLEX

MODEL	HP	PUMP	TANK SIZE	CFM @ 80 PSI	WEIGHT (Lbs.)
3DA3	0.75	ES06	30	2.1	255
6DG5	1.5	E23	60	4.1	470
8DJ7	3	ES30	80	7.5	615
8DN8	3	ES50	80	11.3	725
12DN9	5	ES50	120	15.2	950

CURTIS-TOLEDO, INC.

1905 KIENLEN AVENUE | ST. LOUIS, MO 63133

314-383-1300

WWW.FSCURTIS.COM | INFO@FSCURTIS.COM