

FEATURES AND BENEFITS

QUALITY COMPONENTS

Built to the highest levels of performance and reliability.

- Superior durability handles even the most demanding applications
- High-efficiency separation and filtration for long life
- Generously sized components for the utmost in reliability and maximum uptime
- Rugged sub-frame for years of trouble-free operation

SUPERIOR PACKAGE DESIGN

Robust design ensures maximum uptime.

- Open design offers easy access to all components—no need to remove panels or brackets
- Rugged and leak-free design
- Easy servicing for low cost of ownership

LOW POWER CONSUMPTION

Designed for outstanding efficiency.

- Exclusive slow-speed airend profile results in higher air delivery while reducing power consumption
- Proven control technology for power savings and pressure stability in all demand loads



- NEMA Premium Efficiency motors
- Low internal pressure drop increases efficiency

CUSTOMER-FOCUSED ENGINEERING

Flexibility to meet your specific needs.

- Open design allows flexibility for meeting the needs of unique applications
- Large range of factory options to fit individual needs

TECHNICAL DATA

MODEL	CAPACITY FAD* (CFM)				MOTOR HP	TANK Gal.	DIMENSIONS L x W x H - In.	WEIGHT (UNENCLOSED) Lbs.
	100 psi	125 psi	150 psi	175 psi				
RSB-15B	69	59	51	45	15	-	60 x 41 x 39	940
RSB-15T	69	59	51	45	15	80	73 x 41 x 65	1175
RSB-20B	92	81	76	65	20	-	60 x 41 x 39	985
RSB-20T	92	81	76	65	20	120	73 x 41 x 65	1305
RSB-25B	111	101	92	84	25	-	60 x 41 x 39	1060
RSB-25T	111	101	92	84	25	120	77 x 41 x 69	1380
RSB-30B	135	125	113	101	30	-	60 x 41 x 39	1150
RSB-30T	135	125	113	101	30	120	77 x 41 x 69	1420
RSB-40B	189	173	150	140	40	-	72 x 53 x 44	1425
RSB-40T	189	173	150	140	40	200	80 x 53 x 81	1745
RSB-50B	220	204	186	170	50	-	72 x 53 x 44	1600
RSB-50T	220	204	186	170	50	200	80 x 53 x 81	1920
RS50D	240	202	176	165	50	-	72 x 42 x 46	1925
RS60D	280	275	236	199	60	-	76 x 48 x 60	2170
RS75D	357	330	312	260	75	-	84 x 54 x 60	2690
RS100D	457	438	374	337	100	-	84 x 54 x 60	2950
RS125D	600	534	475	440	125	-	84 x 66 x 68	4520
RS150D	742	706	583	546	150	-	84 x 66 x 68	4750
RS200D	920	860	770	680	200	-	90 x 80 x 75	5250
RS250D	1170	1050	980	890	250	-	112 x 80 x 78	8900
RS300D	1350	1300	1150	1090	300	-	112 x 80 x 78	9200